

Jack PC - Thin Clients

model	EFI6700	EFI6800	EFI6900
Operating System	Windows CE .NET 4.2/5	Windows CE .NET 4.2/5	Windows CE .NET 4.2/5
Class	LAN-Integrated, PoE	LAN-Integrated, PoE	LAN-Integrated, PoE
CPU	AMD Au 1550 RISC	AMD Au 1550 RISC	AMD Au 1550 RISC
CPU FSB	333 MHz	500 MHz	500 MHz
Equiv. x86	800 MHz	1.2 GHz	1.2 GHz
Flash/RAM	32/64 MB	64/128 MB	64/128 MB
Video Memory	4 MB	8 MB	8 MB
Video Output	Analog	Analog	DVI/Analog (Dual screen support)
Audio Support	In/Out 20-bit Stereo	In/Out 20-bit Stereo	In/Out 20-bit Stereo
USB Ports	4	4	4
Max Resolution	1280x1024 pixels	1280x1024 pixels	1600x1200 pixels (Future support)
Max Colors	16 M (24 bit)	16 M (24 bit)	16 M (24 bit)
Description	LAN-Integrated, Power-over-Ethernet thin client, entry level. EU/UK Wall Mounting, IDC Term. Wiring	LAN-Integrated, Power-over-Ethernet thin client, high-end. EU/UK Wall Mounting, IDC Term. Wiring	LAN-Integrated, Power-over-Ethernet thin client, high-end + DVI+ Dual screen support. EU/UK Wall Mounting, IDC Term. Wiring
Chip PC PN	CPN02031	CPN02032	CPN02033

Jack PC - Evaluation Kits

All you need to install and evaluate Jack PC - conveniently packed and attractively priced!

model	Evaluation Kit EFI-6700	Evaluation Kit EFI-6800	Evaluation Kit EFI-6900
Jack PC	1 Jack PC EFI - 6700	1 Jack PC EFI - 6800	1 Jack PC EFI - 6900
Software	Xcalibur Global Management Software Evaluation DVD & Installation CD	Xcalibur Global Management Software Evaluation DVD & Installation CD	Xcalibur Global Management Software Evaluation DVD & Installation CD
Powering	* Power supply * PowerDsine Kit, including Power-over-Ethernet Tester and Midspan Injector	* Power supply * PowerDsine Kit, including Power-over-Ethernet Tester and Midspan Injector	* Power supply * PowerDsine Kit, including Power-over-Ethernet Tester and Midspan Injector
Installation Tools	* 2 IDC Termination Kits for new LAN installation * 2 RJ-45 Termination Kits for existing LAN installation * 2 double RJ-45 LAN Cables * 2 Jack PC Housings * 2 Extraction Tools * IDC Punch-Down Tool for wiring	* 2 IDC Termination Kits for new LAN installation * 2 RJ-45 Termination Kits for existing LAN installation * 2 double RJ-45 LAN Cables * 2 Jack PC Housings * 2 Extraction Tools * IDC Punch-Down Tool for wiring	* 2 IDC Termination Kits for new LAN installation * 2 RJ-45 Termination Kits for existing LAN installation * 2 double RJ-45 LAN Cables * 2 Jack PC Housings * 2 Extraction Tools * IDC Punch-Down Tool for wiring
Accessories	* USB to 2 PS/2 ports adapter * USB-to-1 Serial (RS-232) port adapter	* USB to 2 PS/2 ports adapter * USB-to-1 Serial (RS-232) port adapter	* USB to 2 PS/2 ports adapter * USB-to-1 Serial (RS-232) port adapter * DVI to VGA adapter * Dual-screen Y Cable DVI-I to DVI-D and DVI-A * Dual-screen Y Cable DVI-I to DVI-D and VGA
Others	Technical Documentation Marketing Materials High Quality Carry Bag	Technical Documentation Marketing Materials High Quality Carry Bag	Technical Documentation Marketing Materials High Quality Carry Bag
Chip PC PN > EU power	CPN02085	CPN02086	CPN02087
Chip PC PN > UK power	CPN02240	CPN02241	CPN02242



Xtreme PC - Thin Clients

Model	EX5070	EX5452	EX5450
EU/UK Description	Xtreme PC EX 5070 EU/UK Power, Single Pack	Xtreme PC EX 5452 with Integrated PKI Smart Card EU/UK Power, Single Pack	Xtreme PC EX 5450 EU/UK Power, Single Pack
Class	Entry level	Integrated PC/SC Smart Card Reader Supporting PKI Solutions	High-end
Operating System	WIN CE.NET 4.2/5	WIN CE.NET 4.2/5	WIN CE.NET 4.2/5
Form Factor	Miniature	Miniature	Miniature

Hardware Configuration

Processor	333 MHz AMD RISC Processor (Equiv. to 500 MHz x86)	400 MHz AMD RISC Processor (Equiv. to 800 MHz x86)	400 MHz AMD RISC Processor (Equiv. to 800 MHz x86)
FLASH(DOC)/SDRAM	16/64 MB	32/64 MB	32/64 MB
Video memory	4 MB	4 MB	4 MB
Max Resolution	1280x1024 at 16M (24bit); 70 Hz	1280x1024 at 16M (24bit); 70 Hz	1280x1024 at 16M (24bit); 70 Hz

I/O Interfaces

Network	Ethernet 10/100	Ethernet 10/100	Ethernet 10/100
USB Ports	3	3	3
Serial/Parallel	1/1	1/1	1/1
PS/2	USB to PS/2 Adapter (at additional cost)	USB to PS/2 Adapter (at additional cost)	USB to PS/2 Adapter (at additional cost)
Local Multimedia Support		√	√
Audio Support	* 20-bit Stereo * Audio-Out/In	* 20-bit Stereo * Audio-Out/In	* 20-bit Stereo * Audio-Out/In
Power Consumption	4W	5W	5W

Local Software

Desktop with Windows XP Look & Feel	√	√	√
Fully, Remotely managed desktop	√	√	√
Upgradeable Modular Image	√	√	√
Latest ICA / RDP/ IE	√	√	√

Chip PC PN > EU power	CPN01714	CPN00492	CPN00486
Chip PC PN > UK power	CPN01812	CPN00500	CPN00494

Solution Evaluation Kits

Model	Evaluation Kit EX-5070	Evaluation Kit EX-5452
Description	* Xtreme PC EX-5070 * Xcalibur Evaluation DVD * Marketing materials * EU/UK Power	* Xtreme PC EX-5452 (model with Integrated PC/SC smart card reader/writer) * Xcalibur Evaluation DVD * Marketing materials * EU/UK Power
Chip PC PN > EU power	CPN02067	CPN01847
Chip PC PN > UK power	CPN02068	CPN01849

